

9USB




Classe 9USB has an eye-catching, futuristic design and is made from tough materials, such as stainless steel and aluminium, so it's packed with character.

Shock-absorbing side panels guarantee a sturdy machine that's practical to use.

Available with 2, 3 and 4 groups and also in a TALL version.



Classe 9USB features advanced electronics and an alphanumeric display for managing the machine's main settings.



Innovative functional elements like the soft-touch button control and ergonomic lighting assist the barista in every phase of use and cleaning.



The hot-water temperature control system for tea and infusions has two different temperatures and programmable dosing.



Stunning lights on the steel side panels and the floating front panel accentuate the design, lending the machine a strikingly elegant yet bold and trendy look.



Classe 9USB has an ergonomic lighting system in the work area to make the barista's job easier plus chrome group covers and all the distinctive stylish accessories from the Rancilio range.



Classe 9USB - 3 groups



Technical Features

- independent heat exchangers
- electric heating
- built-in volumetric pump
- pump pressure gauge
- boiler pressure gauge
- electronic water level control
- electronic boiler pressure control
- multifunctional onboard computer with display and USB port
- low-voltage brew heads (24 V)
- low-voltage dispensing controls (24 V)
- Also available in a "TALL" version
- LED lights illuminate the work area, functional LED lights on the group button panels, stylish lateral lighting

Standard features, accessories

- STANDARD FEATURES:** 1 filter holder for 2 cups per group, 1 filter holder for 1 cup, 2 steam wands, 1 mixed hot water dispenser with two buttons for programmable time-controlled dosing and/or temperature (4-TEA), coffee tamper, measuring scoop and cleaning discs, levelling feet
- ACCESSORIES:** automatic or manual DP water softener, MD dosing grinder

Materials

aluminium and stainless steel body

Technical Data

2 GROUPS

dimensions (W-D-H) 750x540x523 mm (29.53x21.26x20.58 in)	weight 74 kg (163 lb)	boiler 11 Lt (2.42 ukgal)
boiler power 3200 W (120 V) - 4300 W	voltage 120 / 220-240 / 380-415 3N	frequency 50/60 Hz

3 GROUPS

dimensions (W-D-H) 990x540x523 mm (38.98x21.26x20.58 in)	weight 85 kg (187 lb)	boiler 16 Lt (4.24 ukgal)
boiler power 6000 W	voltage 220-240 / 380-415 3N	frequency 50/60 Hz

4 GROUPS

dimensions (W-D-H) 1230x540x523 mm (48.42x21.26x20.58 in)	weight 96 kg (211 lb)	boiler 22 Lt (4.84 ukgal)
boiler power 6000 W	voltage 220-240 / 380-415 3N	frequency 50/60 Hz

Standard



Ergonomic steam control



Rapid setting



Automatic steam wand



Smart power management



Electric cup warmer



Pod and Capsule Adaptor



Voltage stabilizer



Automatic washing programme



Advanced diagnostics



Temperature programming



Intertek



Intertek