# **CHEESE TABLES**

# Cheese table, type SM

Basic cheese table on a stable support with an edge of 40 mm Material: stainless steel AISI 304



Туре
SM-97
SM-147
SM-199
SM-249
SM-299

#### Additional equipment:

- deposit shelf under the table
- draining grid under the table
- support on wheels

# Cheese table - heated, type SMG

Cheese table on a stable support with a heated working plane. Connection to water supply. With this system we prevent the sudden cooling of the cheese grain when it comes in contact with the cold surface of stainless steel.

Material: Stainless steel AISI 304



#### Type SMG-97 SMG-147 SMG-199 SMG-249 SMG-299

#### Additional equipment:

- deposit shelf under the table
- draining grid under the table
- support on wheels



PLEVNIK production and marketing d.o.o. Podsmreka 56, 1356 Dobrova, Slovenia Tel.: 00386 / (0)1 200 60 80 Fax.: 00386 / (0)1 257 44 22

E-mail.: info@plevnik.si, http://www.plevnik.si

REPRESENTATIVE

## Cheese model table, type SDM

It is used for the direct filling of cheese models by pouring cheese curd and whey into the table.

Material: stainless steel AISI 304

Composition: deepened cheese table, support on wheels, outflow valve for whey, basic dividing plate with a 100 mm edge (for cheese up to 3 kg)



Additional equipment :
- deposit shelf under the ta

- able
- draining grid under the table
- draining perforated grid at the bottom of the table
- extra dividing plate (for a different size of cheese)

Туре	Processing capacity (kg)
SDM-1010	cca. 40
SDM-1510	cca. 70
SDM-2010	cca. 90
SDM-2510	cca. 120
SDM-3010	cca. 140

Table depth: 200 mm

The dividing plate Ø180 mm is suitable for cheese models with an outside diameter up to 240 mm (cheese of cca. 3 kg) The dividing plate Ø140 mm is suitable for cheese models with an outside diameter up to 195 mm (cheese of cca. 2 kg)

### Cheese draining table, type SOM

The cheese draining table is used for the draining of cheese curd into a single cheese block. The cheese curd with whey is poured in the place bounded by two draining grids (the distance between the grinds can be adjusted regarding to the quantity of curd). After the draining the cheese block is manually cut into smaller pieces that will be putted in cheese forms.

Material: AISI 304

Composition: deepened cheese table, support on wheels, side draining grids, outflow valve



#### Additional equipment:

- deposit shelf under the table
- draining grid under the table
- draining stainless steel grid at the bottom of the table

Туре	Processing capacity (kg)
SOM-109	cca. 60
SOM-159	cca. 90
SOM-209	cca. 120
SOM-2510	cca. 150
SOM-3010	cca. 190

Table depth: 350 mm



PLEVNIK production and marketing d.o.o. Podsmreka 56, 1356 Dobrova, Slovenia Tel.: 00386 / (0)1 200 60 80

Fax.: 00386 / (0)1 257 44 22

E-mail.: info@plevnik.si, http://www.plevnik.si

REPRESENTATIVE